

TM600

Hög belastningskapacitet och dragkraft
God komfort på väg
Minimal markpackning
Utmärkt självrensning

Trelleborg TM600.

Tekniska specifikationer

Dimension	Mönster	SW mm	OD mm	SLR mm	RC mm	SRI mm	Fälg	Slang
280/85R20 112A8 (109B) (11.2R20)	TM600	292	984	446	2952	475	W10 W9 - W8 - DW10	Slanglöst
320/85R20 119A8 (116B) (12.4R20)	TM600	329	1052	470	3160	500	W11 W10 - W9 - DW11	Slanglöst
280/85R24 115A8 (112B) (11.2R24)	TM600	292	1086	494	3276	525	W10 W9 - W8 - DW10	Slanglöst
320/85R24 122A8 (119B) (12.4R24)	TM600	329	1154	515	3465	550	W11 W10 - W9 - DW10 - DW11	Slanglöst
340/85R24 125A8 (122B) (13.6R24)	TM600	353	1188	540	3547	575	W12 W11 - DW11 - DW12	Slanglöst
380/85R24 131A8 (128B) (14.9R24)	TM600	390	1256	560	3750	600	W13 W12 - W11 - DW11 - DW12 - DW13	Slanglöst
420/85R24 137A8 (134B) (16.9R24)	TM600	438	1324	590	3970	625	W15L W14L - DW14L - DW15L	Slanglöst
280/85R28 118A8 (115B) (11.2R28)	TM600	292	1187	542	3580	575	W10 W9 - DW10	Slanglöst
320/85R28 124A8 (121B) (12.4R28)	TM600	329	1255	566	3796	600	W11 W10 - W9 - DW10 - DW11	Slanglöst
340/85R28 127A8 (124B) (13.6R28)	TM600	353	1289	595	3885	625	W12 W11 - DW11 - DW12	Slanglöst
380/85R28 133A8 (130B) (14.9R28)	TM600	390	1357	615	4085	650	W13 W12 - W11 - DW11 - DW12 - DW13	Slanglöst
420/85R28 139A8 (136B) (16.9R28)	TM600	438	1425	635	4290	675	W15L W14 - DW14L - DW15L	Slanglöst
380/85R30 135A8 (132B) (14.9R30)	TM600	390	1408	635	4238	675	W13 W12 - W11 - DW11 - DW12 - DW13	Slanglöst
420/85R30 140A8 (137B) (16.9R30)	TM600	438	1475	660	4455	700	W15L W14 - DW14L - DW15L	Slanglöst
460/85R30 145A8 (142B) (18.4R30)	TM600	475	1544	691	4678	725	W16L W15L - DW15L - DW16L	Slanglöst
420/85R34 142A8 (139B) (16.9R34)	TM600	438	1578	715	4745	750	W15L W14 - DW14L - DW15L	Slanglöst
460/85R34 147A8 (144B) (18.4R34)	TM600	475	1646	745	4945	775	W16L W15L - DW15L - DW16L	Slanglöst
320/85R38 129A8 (126B) (12.4R38)	TM600	325	1520	690	4605	750	W11 W10 - W9 - DW10 - DW11	Slanglöst
340/85R38 133A8 (130B) (13.6R38)	TM600	353	1543	710	4665	750	W12 W11 - DW11 - DW12	Slanglöst
420/85R38 144A8 (141B) (16.9R38)	TM600	438	1679	760	5060	800	W15L W14L - DW14L - DW15L	Slanglöst
460/85R38 149A8 (146B) (18.4R38)	TM600	475	1747	800	5260	825	W16L W15L - DW15L - DW16L	Slanglöst
520/85R38 155A8 (152B) (20.8R38)	TM600	536	1849	825	5510	875	DW18L W16L - W18L - DW16L	Slanglöst
480/80R42 151A8 (151B) (18.4R42)	TM600	495	1850	833	5550	875	W16A 16DD - DW16A	Slanglöst
520/85R42 157A8 (157B) (20.8R42)	TM600	536	1952	881	5867	925	DW18L W16L - W18L - DW16L	Slanglöst
480/80R46 158A8 (158B) (18.4R46)	TM600	495	1964	887	5950	925	W16A 16DD - DW16A	Slanglöst



TRELLEBORG

Trelleborg Wheel Systems

231 81 Trelleborg, Besöksadress: Henry Dunkers gata 1
Tel: 0410-510 00 - Fax: 0410-139 96
www.trelleborg.com/wheelsystems_se